



Wall Bricks Waves

Sizes	Lb/Sq.ft	Sq.ft x Package
H 3.54 in, W 9.44 in, D 0.35 in	3.69	10.76

BENEFITS



Resistant to all environments.



Do not propagate fire.



For any type of climate.



High impact resistant.

APPLI CATIONS

- **Houses.**
- **Commercial Center.**
- **Storages/ Industrial Plants.**
- **Public Places.**

Due to the manufacturing process used in the production of stoneware tiles, variations in shade and size are normal and acceptable. Therefore, at the time of installation, it is advisable to mix the contents of several packages to achieve optimal results in the selected shade range.
The support surface must meet the technical specifications according to the intended use of the space, must be well-leveled, and free from moisture or contaminating dust.
The minimum gap recommended is 0.27" to 0.39".
It is advisable to clean as you go during installation. Cleaning should be done with a damp sponge or cloth. This prevents staining of the product and facilitates the final cleaning.
Never use muriatic acid, detergents, or ACPM; these products can burn, stain, and prematurely degrade the Thin Brick.
The company will not be responsible for poor installation or defects caused by improper handling of the product at any stage (storage, installation, cleaning, and maintenance).

IMPORTANT

- Storage should be done indoors.
- The warehouse must be free from grease and moisture and on a flat surface.
- Place the product so that it rests on its edge, never lying flat.
- It is recommended to stack no more than 2 pallets high.

CERTIFICATION

